

(19)

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 849 928 A2**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:

24.06.1998 Bulletin 1998/26

(51) Int Cl.<sup>6</sup>: **H04M 11/06, H04Q 11/04**

(21) Application number: **97309877.5**

(22) Date of filing: **08.12.1997**

(84) Designated Contracting States:

**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE**

Designated Extension States:

**AL LT LV MK RO SI**

(72) Inventors:

- **Nye, Robert Alan**  
**Plainfield, Illinois 60544 (US)**
- **Posthuma, Carl Robert**  
**Wheaton, Illinois 60187 (US)**

(30) Priority: **19.12.1996 US 767138**

(71) Applicant: **LUCENT TECHNOLOGIES INC.**  
**Murray Hill, New Jersey 07974-0636 (US)**

(74) Representative: **Johnston, Kenneth Graham et al**  
**Lucent Technologies (UK) Ltd,**  
**5 Mornington Road**  
**Woodford Green Essex, IG8 OTU (GB)**

(54) **Telecommunication equipment support of high speed data services**

(57) A line interface unit terminates individual subscriber lines and supports conventional telephone service and high speed data service. It provides an interface between subscriber customer premises equipment and

central office equipment. The use of large diplex filters is not required in order to terminate subscriber lines at the central office while providing high speed data services.

**EP 0 849 928 A2**

## Description

### Background of the Invention

This invention relates to telecommunications equipment which terminates subscriber lines and supports high speed data service for subscribers. The invention is especially suited, but not limited to, providing high speed data services which exceed the capability of conventional POTS terminating equipment.

In the United States, subscribers are commonly provided with telephone services known as plain old telephone services (POTS). Such services include providing conventional dial-tone and automated dialing features including the use of dual frequency tone signaling to communicate dialed number information. Additional modern telephone features including conferencing, call waiting, incoming caller identification, and other commercially available features.

Subscribers utilize a POTS line to carry conventional modem signals controlled by a personal computer to another modem via the public switch telephone network. Modems are currently available which advertise data communication rates up to 33.6 kilobits per second over dial-up analog subscriber lines. Now modems have been announced which are to be capable of data communications up to 56 kilobits per second. Those skilled in the art will understand that the maximum data rate which can be transmitted using modems over a POTS subscriber line is limited by the sampling rate, the bandwidth of the channel, and the rate by which the analog signals are converted to digital signals by the line card units which terminate each POTS line at a central office. Thus, conventional modem data rates are limited by the POTS line cards which terminate the subscriber lines.

It is well known that subscribers in the United States can lease special subscriber lines from their telephone providers which accommodate higher data rates than are supported by conventional dial-up subscriber lines. Such higher speed lines utilize different terminating circuitry at the central office to accommodate higher data rates. For example, integrated services digital network (ISDN) terminating equipment will provide a subscriber with the capability of higher data rates than a conventional POTS terminated line. The known asynchronous digital subscriber line (ADSL) technique which is supported by available equipment provides a significantly higher data rate to a subscriber over a conventional copper two-wire subscriber line. Of course, the ADSL service requires proper terminating equipment at the central office and at the consumer premises to accommodate the greater throughput capabilities, i.e. data rates.

FIG. 1 illustrates currently available services in the United States to subscribers using conventional two wire copper loops. Equipment to the right of dashed line 10 represents customer premises equipment (CPE); equipment to the left of line 10 represents central office line termination equipment. The POTS line interface 12,

also known as a line card, provides an interface between digital incoming and outgoing communication lines 14 and 16, and analog signals carried on subscriber line 18. For example, lines 14 and 16 may carry 64 kilobit per second pulse code modulation (PCM) signals representative of analog information received from and transmitted to line 18. A main distribution frame (MDF) 20 is used to interconnect a plurality of incoming subscriber lines to various terminating equipment at the central office. In this example, line 18 is connected through a diplex filter 19 and MDF 20 to subscriber line 22. A conventional telephone instrument 24 at the consumer's premises is connected through diplex filter 23 to subscriber line 22.

FIG. 1 also illustrates another service to the subscriber which provides a high speed data capability. An ADSL interface circuit 26 provides an interface between the central office and the subscriber for transmitting and receiving data at rates up to several Megabits per second. Lines 28 and 30 provide inbound and outgoing digital data communications representative of information to and from the subscriber carried on line 32. Line 32 is connected via diplex filter 19 and MDF 20 to subscriber line 22. An ADSL interface 36 provides an interface between conventional digital data communicated with a user's personal computer 38 and ADSL analog format signaling communicated on line 37. The diplex filter 23 couples the ADSL signal between ADSL interface 36 and subscriber line 22. The advantage to the user is that the ADSL facilities support a substantially higher data rate than would be available if the subscriber utilized communications terminated via the POTS line interface 12.

A disadvantage illustrated in FIG. 1 is that diplex filters 19 and 23 are required. These known diplex filters function to separate the higher frequency signals associated with ADSL signaling from the lower frequency signals (typically < 4 Kiloherzt) associated with the conventional POTS communications. The conventional diplex filters consist of a lattice of inductors and capacitors that provides the needed filtering while maintaining direct current (DC) continuity required to support battery feed current for POTS service. Because of the DC which must be carried and the voltages which are encountered, such as during ringing, the inductors used in the diplex filters occupy a relatively large volume. Thus, a conventional diplex filter occupies a significant amount of space, for example about 90 cubic centimeters. The size of these filters and the wiring associated with connecting them to the MDF, ADSL interface, and the POTS line interface take up precious space in the terminating equipment cabinets where space is limited. This problem is magnified as more and more subscribers request such service. Therefore, a need exists to provide such high speed services while minimizing the space and wiring requirements especially at the terminating equipment.

### Summary of Invention

It is an object of the present invention to address the above referenced need by providing a solution which minimizes the space and wiring associated with the central office terminating equipment for high speed data services.

In accordance with one embodiment of the present invention, access interface units terminate subscriber lines by which the corresponding subscribers can utilize POTS services and/or high speed data services such as ADSL. The access interface units support both types of service without utilizing a conventional diplex filter. The access interface units include a line support circuit wherein two way communications on the subscriber loop are separated into inbound and outbound communications on separate channels. The inbound communications are split into first and second signals. The first signal is low pass filtered and converted into digital format signals by a Codec. The second signal is high pass filtered and converted into digital format signals by a high speed data receiver. The outbound communications is the summation of third and fourth analog signals from a Codec and high speed data transmitter. An important aspect of this invention resides in the ability to use conventional low voltage, low current passive and active components for the low pass and high pass filters. These filters do not have to accommodate high voltage ringing signals nor the DC battery feed current needed by POTS telephones since the high voltage ringing signals and battery feed are provided by the line support circuit.

### Brief Description of the Drawings

FIG. 1 illustrates a prior art implementation in which a subscriber is provided POTS and high speed data services by using a diplex filter to support line termination equipment.

FIG. 2 illustrates an embodiment of the present invention where an access interface unit accommodates POTS and high speed data services over a single subscriber line without requiring a conventional diplex filter at the terminating central office equipment.

FIG. 3 illustrates an exemplary embodiment of the line support circuit as shown in FIG. 2.

FIG. 4 illustrates another embodiment of the present invention in which a multiple line interface unit terminates several subscriber lines and shares high speed data resources among the subscriber lines.

### Detailed Description

In accordance with the present invention, a single subscriber line supports at least two different classes of subscriber service, e.g. POTS and high speed data services such as XDSL. The "X" in XDSL represents one of a family of digital subscriber line services, such as

ADSL (Asynchronous), RDSL (Rate-adaptive), and VDSL (Very high speed). As used herein "high speed data interface" refers to apparatus that uses a signaling method to provide higher data transmission speeds than can be supported by conventional POTS line terminating equipment.

Referring to FIG. 2, consumer premises equipment is located to the right of dashed line 40; central office equipment including line terminating equipment is located to the left of dashed line 40. A two-wire copper subscriber line 42, also known as a subscriber loop, connects consumer premises equipment located to the right of line 40 with central office terminating equipment to the left of line 40. The subscriber may utilize a conventional telephone instrument 44 which can be connected to subscriber line 42 via a diplex filter 43 to receive POTS. The subscriber may elect to couple a high speed data interface, e.g., XDSL interface 46, via diplex filter 43 to subscriber line 42 to support high speed data communications. A personal computer 48 is illustratively shown connected to XDSL interface 46. It will be appreciated by those skilled in the art that equipment other than personal computer 48 may be utilized to transmit or receive a variety of data representing different types of information.

An access interface unit (AIU) 50 terminates subscriber line 42 via MDF 52. The AIU 50 is responsible for all interactions and communication signals transmitted to and received from subscriber line 42. Additionally, AIU 50 is responsible for providing separate inbound and outbound data paths for communicating information with the central office switch such as utilizing PCM encoded digital signals or asynchronous transfer mode (ATM) format signals. Communication channels 54 and 56 carry inbound and outbound high speed digital information, respectively. Communication channels 58 and 60 similarly carry inbound and outbound conventional telephone information, respectively.

Line support circuit 62 terminates subscriber line 42 and provides conventional POTS subscriber line support facilities. The line support circuit 62 provides the simplex to duplex communications interface by which duplex communications on subscriber line 42 are separated into independent transmit and receive communications coupled to the central office. Line 64 carries information from the subscriber and line 66 carries information to be transmitted to the subscriber. Line 64 is coupled to signal splitter 68 which splits the information received from the subscriber into two substantially equal signals, one signal being applied to line 70 and the other signal being applied to line 72. Line 70 is coupled to high pass filter 74 and line 72 is coupled to low pass filter 76. The outputs from the high pass filter 74 and low pass filter 76 are coupled respectively to the XDSL receiver 78 and CODEC (COder-DECoder) 80. The low pass filter 76 passes signals with frequencies relevant for conventional voice communication, such as below four Kiloherztz, to the CODEC which translates the analog voice

sociated with the high speed data can be incorporated into the interface units 142A...142M. Alternatively, such filtering could be accomplished in the analog domain before conversion of the analog signals associated with the line support unit into digital signals. In that case, the filtered analog signals would be sent via lines 148A...148N to the HSDU and the interface units 142A...142M would process the filtered analog signals. An important aspect of the invention resides in not having to provide such filtering at the "front end" of the line support circuit where ringing signals and battery feed requirements place further demands on such filtering.

A controller 150 provides call processing communications and instructions among the central office via line 152, HSDU 140 via line 154, and the SIUs via line 156. A microprocessor 158 is supported by read only memory (ROM) 160, and random access memory (RAM) 162. The microprocessor 158 is connected to input/output interface 164 which supports the receipt and transmission of signals over lines 152, 154 and 156. Call processing instructions and status information are communicated on line 152 between the central office and MLIU 120 via controller 150. Instructions are communicated on line 154 to HSDU 140 to control the path selections made by selector 146. Call processing information is carried on line 156 between controller 150 and the SIUs.

It will be apparent to those skilled in the art that various implementations of the present invention is possible. For example, very large scale integration (VLSI) techniques could be used to construct a multiple line interface unit wherein the required functions in the SIUs could be provided in a common shared circuit. A DSP with sufficient power and capabilities could service several if not all of the SIUs. Further, common functions of the XDSL interface units suggest several if not all of these units could be combined into a shared processing circuit or chip. It is also contemplated that the functions of the HSDUs and the SIUs could be combined in whole or in part by a sufficiently powerful DSP or DSPs or a computing system. Alternatively, the internal components of the MLIU could be segregated by analog and digital functions.

An example of a subscriber receiving XDSL services is explained below with regard to the embodiment shown in FIG. 4. The following steps describe providing XDSL services for the subscriber as the called party.

1. The central office equipment sends a call setup message by channel 152 to controller 150. The central office setup message identifies the subscriber line to which high speed data services is to be provided. Controller 150 maintains a stored table that correlates subscriber lines to corresponding subscriber interface units, and hence the SIU to receive XDSL information is known based on the identity of the subscriber line.
2. Controller 150 generates a command transmitted

via communication path 156 to SIU 124A supporting subscriber line 122A. The subscriber served by subscriber line 122A is the party to receive XDSL communications in this illustrative example.

3. Controller 150 generates another command signal transmitted on line 154 to the HSDU 140 (selector 146) which identifies input line 148A to be utilized to provide XDSL communications with line interface unit 124A. Controller 150 stores a table of availability of the interface units 142A ... 142M and assigns a not in use high speed interface unit such as 142A to handle the XDSL communications with subscriber line 122A.

4. Following the establishment of a communication path between the subscriber line 122A and the HSDU 140, controller 150 sends a reply message via channel 152 to the central office equipment confirming that the requested XDSL communication path has been established and identifying the high speed data unit 142A and corresponding line 144A which will carry the subject XDSL communications between the central office equipment and MLIU 120. Thus, a completed path to the central office is now available to carry XDSL communications with customer premises equipment coupled to subscriber line 122A.

In the above example, the controller 150 maintains a database of the availability of the interface units 142A ... 142M to handle an XDSL service request. Alternatively, the central office could maintain a table or database of interface unit availability and provide controller 150 with the identification of the interface unit to be used.

The following steps illustrate the origination of a request by a subscriber for XDSL services implemented on an on demand basis.

1. For this illustrative example, assume that the subscriber requesting XDSL services is associated with subscriber line 122A. Utilizing customer premises equipment coupled to subscriber line 122A, the subscriber will initiate a request for XDSL communications such as by sending a request for services signal to the associated SIU 124A.
2. Using known signal detection techniques, the DSP 132 of SIU 124A will recognize the request for services signal.
3. SIU 124A will then generate a command on line 156 advising controller 150 of the request for XDSL services by the subscriber associated with line 122A.
4. The controller 150 transmits a service request on line 152 to the central office. The central office after checking the availability of one of lines 144A...144M sends an instruction to controller 150 advising of the line, e.g. 144A, to be used in accommodating this request for services.

5. The controller 150 transmits a command signal on line 154 to HSDU 140 (selector 146) indicating the XDSL interface unit 142A to be connected to SIU 124A via line 148A.

6. The controller 150 preferably further generates a command signal on line 156 to SIU 124A to advise of the path completion.

7. Thus, an XDSL communication path is established between the subscriber's customer premise equipment associated with subscriber line 122A and high speed data line 144A which carries simplex inbound and outbound communications to the central office equipment.

It is also contemplated that the high speed services could be provisioned by a telecommunication system administrator, i.e. so called "nailed up". In this circumstance, one of lines 144A... 144M would be assigned on a good until changed basis to one of the SIUs, and hence to a subscriber served by that SIU. In this arrangement, the subscriber would always have immediate access to high speed facilities.

Although an explanation of embodiments of the present invention have been made above with reference to the drawings, the scope of the invention is defined by the claims which follow.

#### Claims

1. A line termination unit in a telecommunications system that supports plain old telephone services (POTS) and high speed data (HSD) services to a subscriber over a common two-wire subscriber line, the line termination unit comprising:

a line support circuit that connects to said common two-wire line and provides battery feed to said line, the line support circuit including means for receiving incoming analog POTS and HSD signals from the line and means for transmitting outgoing analog POTS and HSD signals to the line;

means coupled to the line support circuit for separating the received incoming analog signals into first and second signals where the first signals represent POTS information and the second signals represent HSD information; and means coupled to said separating means for converting the first signals into third digital signals having a format used for POTS signals by an associated central office and transmitting the third digital signals to the central office; means coupled to said separating means for converting the second signals into fourth digital signals having a format used for HSD signals by an associated central office and transmitting the fourth digital signals to the central office.

2. The line termination unit according to claim 1 further comprising:

office interface means for receiving outgoing digital POTS and HSD signals from the central office;

means coupled to the office interface means for converting the outgoing digital POTS signals into fifth signals and for converting the outgoing digital HSD signals into sixth signals where the fifth and sixth signals are analog signals representing POTS information and HSD information, respectively;

means coupled to said converting means for combining the fifth and sixth signals into a combined signal that is coupled to the line support circuit which transmits the combined signal to the subscriber line.

3. The line termination unit according to claim 1 wherein said separating means comprises a first filter which permits said first signals to pass, the first filter does not carry current from said battery feed.

4. The line termination unit according to claim 3 wherein said separating means further comprises a second filter which permits said second signals to pass, the second filter does not carry current from said battery feed.

5. The line termination unit according to claim 1 wherein said line support circuit has sufficient frequency bandwidth to convey the HSD information which requires a higher bandwidth than bandwidth needed to convey the POTS information.

6. The line termination unit according to claim 1 wherein the HSD services consists of asynchronous digital subscriber loop (ADSL) services.

7. A multiple line termination unit in a telecommunications system that supports plain old telephone services (POTS) and high speed data (HSD) services for N subscribers over common two-wire subscriber lines where N is a positive integer greater than one, the multiple line termination unit comprising:

a plurality of subscriber interface units (SIU) for connection to the respective two-wire subscriber lines, each SIU provides battery feed to a respective two-wire subscriber line and includes means for receiving incoming analog POTS and HSD signals from the line and means for transmitting outgoing analog POTS and HSD signals to the line, each SIU provides an interface between analog POTS signals on the associated subscriber line and digitized POTS signals communicated with the central office;

high speed data unit (HSDU) which supports M concurrent HSD channels where M is a positive integer less than N, the HSDU comprises a selector which is coupled to each SIU, the selector controlling which of the SIUs will be coupled to one of said HSD channels. 5

8. The multiple line termination unit according to claim 7 further comprising:

a controller coupled to an associated central office, the HSDU, and each SIU, the controller providing call processing communications including instructions that control the operation of said selector. 10

15

20

25

30


35

40

45

50

55



(PRIOR ART)  
**FIG. 1**




FIG. 2








FIG. 3





Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 849 928 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
08.03.2000 Bulletin 2000/10

(51) Int Cl.7: H04M 11/06, H04Q 11/04

(43) Date of publication A2:  
24.06.1998 Bulletin 1998/26

(21) Application number: 97309877.5

(22) Date of filing: 08.12.1997

(84) Designated Contracting States:  
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventors:  
• Nye, Robert Alan  
Plainfield, Illinois 60544 (US)  
• Posthuma, Carl Robert  
Wheaton, Illinois 60187 (US)

(30) Priority: 19.12.1996 US 767138

(71) Applicant: LUCENT TECHNOLOGIES INC.  
Murray Hill, New Jersey 07974-0636 (US)

(74) Representative:  
Johnston, Kenneth Graham et al  
Lucent Technologies (UK) Ltd,  
5 Mornington Road  
Woodford Green Essex, IG8 OTU (GB)

(54) Telecommunication equipment support of high speed data services

(57) A line interface unit terminates individual subscriber lines and supports conventional telephone service and high speed data service. It provides an interface between subscriber customer premises equipment and

central office equipment. The use of large diplex filters is not required in order to terminate subscriber lines at the central office while providing high speed data services.




FIG. 2



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 97 30 9877

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	COOK J ET AL: "ADSL AND VDSL SPLITTER DESIGN AND TELEPHONY PERFORMANCE" IEEE JOURNAL ON SELECTED AREAS IN COMMUNICATIONS,US,IEEE INC. NEW YORK, vol. 13, no. 9, page 1634-1642 XP000543160 ISSN: 0733-8716 * the whole document *	1,5,6	H04M11/06 H04Q11/04
X	US 5 408 260 A (ARNON EPHRAIM) 18 April 1995 (1995-04-18) * column 2, line 9 - column 3, line 4 * * column 5, line 24 - line 67 *	1,5-7	
X	US 5 534 912 A (KOSTRESKI BRUCE W) 9 July 1996 (1996-07-09) * column 3, line 9 - line 44 * * column 4, line 25 - line 51 *	1,5,6	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04Q H04M
The present search report has been drawn up for a1 claims			
Place of search THE HAGUE		Date of completion of the search 13 January 2000	Examiner Chassatte, R
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons S : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03 02 (P/Cot1)

ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 97 30 9877

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information

13-01-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5408260    A	18-04-1995	CA    2134411 A,C GB    2285564 A,B	12-07-1995 12-07-1995
US 5534912    A	09-07-1996	NONE	

EPO FORM P0558

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 9266

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on .  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-03-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6067316	A	23-05-2000	NONE	
EP 0849928	A	24-06-1998	US 6144659 A	07-11-2000
			EP 0849928 A2	24-06-1998
			JP 10210510 A	07-08-1998



Creation date: 09-08-2004  
Indexing Officer: DHOWARD1 - DAYLN HOWARD  
Team: OIPEBackFileIndexing  
Dossier: 09713745

Legal Date: 06-25-2002

No.	Doccode	Number of pages
1	C.AD	1

Total number of pages: 1

Remarks:

Order of re-scan issued on .....